



**MEGA-INLINER®**  
SYSTEMS



## Mega-Inliner® technical facts

# MEGA-INLINER®

### MEGA-INLINER PACKAGE

- » 50 > 370HL
- » ± 17 KG (250 HL)
- » ± 115 cm length (250 HL)
- » ± 30 cm diameter (250 HL)
- » 2 x 100 µm foil
- » 14 layers (2 x 7)
- » 2 x 0 - 10 µm EVOH (Depending of application)
- » LLDPE in & out side
- » OTR 0,75 cm<sup>3</sup> / m<sup>2</sup>/day 23°C; 75% RH
- » FDA & EU food grade approval
- » Halal & Kosher possible
- » Non-hazardous liquids suitable
- » ISO & SWAP tank container suitable
- » Requires only one man to install and remove
- » ± 5 minutes installation time
- » ± 15 minutes to remove

TANK DIFFERENT  
MOVE EFFICIENT



**MEGA-INLINER®**  
SYSTEMS

## **MEGA-INLINER® IS SAFE & SAVES**

### **CO<sub>2</sub> & Carbon footprint reduction**

- » No need for cleaning & rinsing
- » No loss of potable water
- » No chemical emission
- » No energy consumption for hot water
- » No waiting time costs
- » No Co<sub>2</sub> & Mixed gas lost due to pre pressurizing
- » No need for dedicated tank containers

### **Total freedom in planning**

- » Maximum efficiency
- » No need for previous cargo registration
- » No need for pump unit, use compressed air
- » No need for strategic allocation costs
- » More weight per load

### **Improved quality**

- » No oxidation risk
- » No contamination risk
- » No saturation risk
- » No desaturation risk
- » Produced under N<sub>2</sub> blanket > no enclosed O<sub>2</sub>

### **Certification**

- » FDA & EU food approval
- » Halal & Kosher possible
- » X-ray certificate possible

### **Labour safety**

- » No need to enter the tank container
- » Safer to drive > less sloshing > less fuel consumption
- » No need to go on top of the tank container

**TANK DIFFERENT  
MOVE EFFICIENT**

#### **CONTACT**

+31 40 30 33 030  
info@mega-inliner.com  
mega-inliner.com

#### **OFFICE ADDRESS**

John F. Kennedylaan 9A  
5555 XC Valkenswaard  
The Netherlands