



MEGA-INLINER®
SYSTEMS



Mega-Inliner® technical facts

250HL MEGA-INLINER SYSTEMS

TANK CONTAINER

- » 20' ISO tank container
 - 6.058 x 2.450 x 2.670 mm
- » ± 25.000 ltr / 6604 Gallon
 - up to 30.000 ltr / 7925 Gallon composite SWAP tanks are possible
- » ± 39.000 Kg / 85980 Lbs Gross weight
- » ± 2.750 Kg / 6062 Lbs Tarra weight
- » ± 36.250 Kg / 79917 Lbs Net weight
- » Stainless steel 1.4403, min shell thickness 3,0 mm, dished ends 5,2 mm
- » DN80 In-/Outlet & DN40 Air In-/Outlet
- » 3 Bar work pressure / 4 bar test pressure / 0,2 vacuum rating
- » Non-hazardous liquids only
- » ±1°C Δ per 24 hours with 25°C ambient temp. insulation
- » Reefer unit optional
- » Certifications; all required and mandatory certifications are applied.
- » Track & Tracing
- » Every Mega-Inliner Systems tank will be supplied with the mandatory & required documents and identifications.

**TANK DIFFERENT
MOVE EFFICIENT**



MEGA-INLINER®
SYSTEMS

ADAPTERS:

- ① MI DN80 outlet
» Stainless steel
- ② MI DN80 piercing unit
» Stainless steel
- ③ MI DN80 > 3" BSP adapter
» Ela Flex Male adapter
» Stainless steel
- ④ Vacuum & Sample adapter
» Stainless steel

①



②



③



④



INTEGRATION ASSISTENCE

Mega-Inliner BV and Mega-Inliner Systems BV will assist and takes care of the training to integrate the Mega-Inliner® System in your complete supply chain. Feel free to contact us by phone +31 40 30 33 030 or by e-mail info@Mega-Inliner.com to find out more about the tremendous possibilities the Mega-Inliner® System can provide in significantly reducing your shipping costs and carbon footprint!

**TANK DIFFERENT
MOVE EFFICIENT**

CONTACT

+31 40 30 33 030
info@mega-inliner.com
mega-inliner.com

OFFICE ADDRESS

John F. Kennedylaan 9A
5555 XC Valkenswaard
The Netherlands