



MEGA-INLINER®
TANK DIFFERENT → MOVE EFFICIENT



Mega-Inliner® technical facts

MEGA-INLINER®

MEGA-INLINER PACKAGE

- » 50 > 370 HL
- » ± 17 KG (250 HL)
- » ± 115 cm length (250 HL)
- » ± 30 cm diameter (250 HL)
- » 2 x 100 µm foil
- » 14 layers (2 x 7)
- » 2 x 0 - 10 µm EVOH (Depending of application)
- » LLDPE in & out side
- » OTR 0,75 cm³ / m²/day 23°C; 75% RH
- » FDA & EU food grade approval

- » Halal & Kosher possible
- » Non-hazardous liquids suitable
- » ISO & SWAP tank container suitable
- » Requires only one man to install and remove
- » ± 5 minutes installation time
- » ± 15 minutes to remove

*Convert
today ↗*

**TANK DIFFERENT
MOVE EFFICIENT**



✉ **CONTACT**
+31 40 30 33 030
info@mega-inliner.com
mega-inliner.com

📍 **OFFICE ADDRESS**
John F. Kennedylaan 9A
5555 XC Valkenswaard
The Netherlands



MEGA-INLINER®
TANK DIFFERENT → MOVE EFFICIENT

*Convert
today →*

MEGA-INLINER® IS SAFE & SAVES

CO₂ & Carbon footprint reduction

- » No need for cleaning & rinsing
- » No loss of potable water
- » No chemical emission
- » No energy consumption for hot water
- » No waiting time costs
- » No Co₂ & Mixed gas lost due to pre pressurizing
- » No need for dedicated tank containers

Total freedom in planning

- » Maximum efficiency
- » No need for previous cargo registration
- » No need for pump unit, use compressed air
- » No need for strategic allocation costs
- » More weight per load

Improved quality

- » No oxidation risk
- » No contamination risk
- » No saturation risk
- » No desaturation risk
- » Produced under N₂ blanket > no enclosed O₂

Certification

- » FDA & EU food approval
- » Halal & Kosher possible
- » X-ray certificate possible

Labour safety

- » No need to enter the tank container
- » Safer to drive > less sloshing > less fuel consumption
- » No need to go on top of the tank container

TANK DIFFERENT
MOVE EFFICIENT



✉ **CONTACT**
+31 40 30 33 030
info@mega-inliner.com
mega-inliner.com

📍 **OFFICE ADDRESS**
John F. Kennedylaan 9A
5555 XC Valkenswaard
The Netherlands